











ÜBERSICHT DER VERSABÄNDER

Modell	Versa Linear 600	Versa Linear 1200	Versa Inside 600	Versa Inside 1200	Versa Inside 1200
					
Lichtstrom pro m	600 - 660 lm/m	1200 - 1320 lm/m	600 - 700 lm/m	1200 - 1400 lm/m	1200 - 1400 lm/m
Effizienz Lichtquelle (max.)	110 lm/W	110 lm/W	175 lm/W	175 lm/W	175 lm/W
Leistungsaufnahme (max.)	6 W/m	12 W/m	4 W/m	8 W/m	8 W/m
Lichtfarbe					
Farbwiedergabe/CRI	RA > 90	RA > 90	RA > 90	RA > 90	RA > 90
Länge Band	1200 mm, 3000 mm, 5000 mm, 10000 mm	1200 mm, 3000 mm, 10000 mm	1200 mm, 3000 mm, 5000 mm, 10000 mm, 50000 mm	1200 mm, 3000 mm, 5000 mm, 10000 mm, 50000 mm	5000 mm, 10000 mm, 50000 mm
Max. Länge am Stück	6000 mm	3000 mm	9000 mm	4500 mm	9000 mm
Kürzbar alle	14 mm 21 mm (mw)	14 mm 21 mm (mw)	33 mm	33 mm	50 mm 62,5 mm (mw)
Direktverbinder			✓		
Flexibler Verbinder 50 mm			✓		
Flexibler Verbinder 150 mm			✓		
Einspeiser für Abschnitte			✓		
Anlötleitung für Abschnitte			✓		
Breite / Höhe	7,5 mm / 3 mm	7,5 mm / 3 mm	7,5 mm / 1,5 mm	7,5 mm / 1,5 mm	7,5 mm / 1,5 mm
IP Klasse	IP 20	IP 20	IP 20	IP 20	IP 20