

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 1/20

## REDOCOL Correction Lacquer (various colours)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name/designation:

REDOCOL Correction Lacquer (various colours)

Article No.:

FE61001

UFI:

Y7XE-0561-E00M-9D8N

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Restoration Kit

Relevant identified uses:

**Sector of uses [SU]**

**SU 6a:** Manufacture of wood and wood products

**Product Categories [PC]**

**PC 9:** Coatings and paints, fillers, putties, thinners

**Article categories [AC]**

**AC 11:** Wood articles: furniture

#### \* 1.3. Details of the supplier of the safety data sheet

**distributor:**

**Ostermann UK Ltd**

Stonebridge Cross Business Park

Unit 104 Poinon Way

WR9 0LW Droitwich

United Kingdom

**Telephone:** UK +44 (0) 1905 793 550, Ireland +44

(0) 1905 793 552

**Telefax:** +44 (0) 1905 793 559

**E-mail:** UK sales.uk@ostermann.eu, Ireland

sales.ie@ostermann.eu

**Website:** www.ostermann.eu

**E-mail (competent person):** j.bruns@ostermann.eu

**Manufacturer:**

**FSG Schäfer GmbH**

Boschstraße 14

48703 Stadtlohn

GERMANY

**Telephone:** +49 (0) 25 63 - 93 95 - 0

**Telefax:** +49 (0) 25 63 - 93 95 - 25

**E-mail:** verkauf@fsg-schaefer.de

**Website:** www.fsg-schaefer.de

#### 1.4. Emergency telephone number

UK: Mr. J. Bruns +44 1905 793 550

IR: Mr. J. Bruns +44 1905 793 552, 24h: +49 30 - 30 68 67 00 (National Poison Inform. Centre Berlin) , UK +44 1905 793 550/ IR +44 (0)1905 793 552 (Only available during office hours.)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids ( <i>Flam. Liq. 2</i> )	H225: Highly flammable liquid and vapour.	
Acute toxicity (oral) ( <i>Acute Tox. 4</i> )	H302: Harmful if swallowed.	
Serious eye damage/eye irritation ( <i>Eye Irrit. 2</i> )	H319: Causes serious eye irritation.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	
Carcinogenicity ( <i>Carc. 2</i> )	H351: Suspected of causing cancer.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 2/20

## REDOCOL Correction Lacquer (various colours)

Hazard classes and hazard categories	Hazard statements	Classification procedure
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



**GHS02**  
Flame



**GHS07**  
Exclamation mark



**GHS08**  
Health hazard



**GHS09**  
Environment

Signal word: Danger

Hazard statements for physical hazards	
H225	Highly flammable liquid and vapour.
Hazard statements for health hazards	
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
Hazard statements for environmental hazards	
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information: none

Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
Precautionary statements Response	
P301 + P312	IF SWALLOWED: Call a POISON CENTER/doctor/First aider if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/First aider if you feel unwell.

#### Special rules for supplemental label elements for certain mixtures:

- 10,3 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (oral).
- 15,0 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (dermal).
- 14,2 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (inhalative).
- 12,4 % percent of the mixture consists of components of unknown hazards to the aquatic environment.

### 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

### \* 3.2. Mixtures

#### Description:

Mixture of following listed substances with nonhazardous additions.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 3/20

## REDOCOL Correction Lacquer (various colours)

### Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 123-86-4 EC No.: 204-658-1 Index No.: 607-025-00-1 REACH No.: 01-2119485493-29-0007	<b>n-butyl acetate</b> Flam. Liq. 3 (H226), STOT SE 3 (H336) Warning EUH066 <b>Acute Toxicity Estimate</b> ATE (oral) 10,760 mg/kg ATE (dermal) > 14,112 mg/kg ATE (inhalation, dust/mist) 23.4 mg/L	29 - < 55 weight-%
CAS No.: 108-10-1 EC No.: 203-550-1 Index No.: 606-004-00-4 REACH No.: 01-2119473980-30	<b>4-methylpentan-2-one</b> Acute Tox. 4 (H332), Carc. 2 (H351), Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066 <b>Acute Toxicity Estimate</b> ATE (oral) > 2,000 - ≤ 5,000 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, vapour) 11 mg/L	11 - < 22 weight-%
CAS No.: 64-17-5 EC No.: 200-578-6 Index No.: 603-002-00-5	<b>ethanol</b> Flam. Liq. 2 (H225) Danger <b>Acute Toxicity Estimate</b> ATE (oral) 6,200 mg/kg ATE (inhalation, vapour) 124.7 mg/L	2 - < 5 weight-%
CAS No.: 108-65-6 EC No.: 203-603-9 Index No.: 607-195-00-7	<b>2-methoxy-1-methylethyl acetate</b> Flam. Liq. 3 (H226) Warning <b>Acute Toxicity Estimate</b> ATE (oral) 8,530 mg/kg ATE (dermal) > 5,000 mg/kg	2 - < 4 weight-%
EC No.: 927-241-2 REACH No.: 01-2119471843-32-XXXX	<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H336) Danger <b>Acute Toxicity Estimate</b> ATE (oral) > 15,000 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, dust/mist) > 6.1 mg/L	1 - < 2.09 weight-%
CAS No.: 13463-67-7 EC No.: 236-675-5 Index No.: 022-006-00-2 REACH No.: 01-2119489379-17-0000	<b>titanium dioxide</b> Carc. 2 (H351) Warning <b>Acute Toxicity Estimate</b> ATE (oral) > 2,000 - 25,000 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, dust/mist) 3.43 - 6.82 mg/L	0 - < 0.71 weight-%
CAS No.: 64742-95-6 EC No.: 918-668-5 REACH No.: 01-2119455851-35	<b>Hydrocarbons, C9, aromatics</b> Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336) Danger <b>Acute Toxicity Estimate</b> ATE (oral) 4 - 8 mg/kg ATE (dermal) 3,160 mg/kg	0 - < 0.42 weight-%
CAS No.: 78-83-1 EC No.: 201-148-0 Index No.: 603-108-00-1 REACH No.: 01-2119484609-23	<b>2-methylpropan-1-ol</b> Eye Dam. 1 (H318), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336), Skin Irrit. 2 (H315) Danger <b>Acute Toxicity Estimate</b> ATE (oral) 2,830 - 3,350 mg/kg ATE (dermal) 2,000 mg/kg ATE (inhalation, vapour) 18.18 mg/L	0 - ≤ 0.084002 weight-%

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024






Print date: 2 May 2024

Version: 0.7



Page 4/20

## REDOCOL Correction Lacquer (various colours)

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 1330-20-7 EC No.: 215-535-7 Index No.: 601-022-00-9 REACH No.: 01-2119488216-32	<b>xylene</b> Acute Tox. 4 (H332, H312), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315)   Warning <b>Acute Toxicity Estimate</b> ATE (oral) 4,300 mg/kg ATE (dermal) > 1,700 mg/kg ATE (inhalation, dust/mist) 21.7 mg/L	0 - ≤ 0.04444 weight-%
CAS No.: 70657-70-4 EC No.: 274-724-2 Index No.: 607-251-00-0	<b>2-methoxypropyl acetate</b> Flam. Liq. 3 (H226), Repr. 1B (H360D***), STOT SE 3 (H335)    Danger <b>Acute Toxicity Estimate</b> ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 400 ppmV	0 - ≤ 0.002081 weight-%

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

#### Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/attention if you feel unwell.

#### In case of skin contact:

If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap.

#### After eye contact:

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Rinse cautiously with water for several minutes.

#### Following ingestion:

Rinse mouth. Get medical advice/attention if you feel unwell. Let 1 glass of water be drunken in little sips (dilution effect).

#### Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider. First aider: Pay attention to self-protection!

### 4.2. Most important symptoms and effects, both acute and delayed

Serious eye damage/eye irritation, Dizziness, Dizziness.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).  
Fire extinguishers Fire class B.

#### Unsuitable extinguishing media:

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable, Combustible.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 5/20

## REDOCOL Correction Lacquer (various colours)

### Hazardous combustion products:

In case of fire may be liberated: Carbon dioxide, Carbon monoxide, Pyrolysis products, toxic, carbon black.

In case of fire: Gases/vapours, toxic.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### 5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

##### Personal precautions:

Special danger of slipping by leaking/spilling product. Remove persons to safety.

##### Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

#### 6.1.2. For emergency responders

##### Personal protection equipment:

Personal protection equipment: see section 8.

### 6.2. Environmental precautions

Discharge into the environment must be avoided. Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### For containment:

Soak up inert absorbent and dispose as waste requiring special attention.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up:

Clean with detergents. Avoid solvent cleaners. Water (with cleaning agent).

### 6.4. Reference to other sections

Safe handling: see section 7.

Personal protection equipment: see section 8.

Disposal: see section 13.

### 6.5. Additional information

Use appropriate container to avoid environmental contamination.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Protective measures

##### Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. According to directive 94/33/EC, juveniles are only allowed to handle this product as long as all effects of dangerous substances are prevented. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Wear personal protection equipment (refer to section 8).

##### Fire prevent measures:

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment). Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking.

##### Measures to prevent aerosol and dust generation:

Technical ventilation of workplace.

##### Environmental precautions:

Discharge into the environment must be avoided.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 6/20

## REDOCOL Correction Lacquer (various colours)

### Advices on general occupational hygiene

Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

#### Packaging materials:

Keep/Store only in original container.

#### Requirements for storage rooms and vessels:

Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on storage assembly:

Do not store together with: Strong acid, Base, alkaline materials, Oxidising agent, strong.

#### Storage class (TRGS 510, Germany): 3 - Flammable liquids

#### Further information on storage conditions:

Protect from sunlight. Store in a well-ventilated place.

### 7.3. Specific end use(s)

#### Recommendation:

Keep out of the reach of children.

#### Industrial sector specific solutions:

Solvent-based varnishes/wood glazes, low in aromatics.

#### GISCODE:

M-KH03

## SECTION 8: Exposure controls/personal protection

### \* 8.1. Control parameters

#### 8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IE from 18 May 2021	<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	① 50 ppm (241 mg/m <sup>3</sup> ) ② 150 ppm (723 mg/m <sup>3</sup> ) ⑤ IOELV
IOELV (EU) from 20 Nov 2019	<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	① 50 ppm (241 mg/m <sup>3</sup> ) ② 150 ppm (723 mg/m <sup>3</sup> )
IE	<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	① 20 ppm (83 mg/m <sup>3</sup> ) ② 50 ppm (208 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin) Sk, IOELV
IOELV (EU)	<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	① 20 ppm (83 mg/m <sup>3</sup> ) ② 50 ppm (208 mg/m <sup>3</sup> )
WEL (GB)	<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	① 50 ppm (208 mg/m <sup>3</sup> ) ② 100 ppm (416 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)
IE from 5 Dec 2011	<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	② 1,000 ppm
WEL (GB)	<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,920 mg/m <sup>3</sup> )

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 7/20

## REDOCOL Correction Lacquer (various colours)

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IE	<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (275 mg/m <sup>3</sup> ) ② 100 ppm (550 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin) SK, IOELV
IOELV (EU)	<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (275 mg/m <sup>3</sup> ) ② 100 ppm (550 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)
WEL (GB)	<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (274 mg/m <sup>3</sup> ) ② 100 ppm (548 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)
IE	<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	① 10 mg/m <sup>3</sup> ⑤ (inhalable fraction)
IE	<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	① 4 mg/m <sup>3</sup> ⑤ (respirable fraction)
WEL (GB)	<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	① 10 mg/m <sup>3</sup> ⑤ (inhalable fraction)
WEL (GB)	<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	① 4 mg/m <sup>3</sup> ⑤ (respirable fraction)
WEL (GB)	<b>Hydrocarbons, C9, aromatics</b> CAS No.: 64742-95-6 EC No.: 918-668-5	① 500 mg/m <sup>3</sup> ⑤ (hydrocarbons, aromatic)
IE	<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	① 50 ppm (150 mg/m <sup>3</sup> ) ② 75 ppm (225 mg/m <sup>3</sup> )
WEL (GB)	<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	① 50 ppm (154 mg/m <sup>3</sup> ) ② 75 ppm (231 mg/m <sup>3</sup> )
IE	<b>xylene</b> CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m <sup>3</sup> ) ② 100 ppm (442 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin) Sk, IOELV
IOELV (EU)	<b>xylene</b> CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m <sup>3</sup> ) ② 100 ppm (442 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)
WEL (GB)	<b>xylene</b> CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (220 mg/m <sup>3</sup> ) ② 100 ppm (441 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 8/20

## REDOCOL Correction Lacquer (various colours)

### 8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
BMGV (GB)	<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	20 µmol/L	① 4-methylpentan - 2-one ② urine ③ end of exposure or end of shift
BMGV (GB) from 30 Nov 2022	<b>xylene</b> CAS No.: 1330-20-7 EC No.: 215-535-7	650 mmol/mol creatinine	① methyl hippuric acid ② urine ③ end of exposure or end of shift

### 8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	48 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	102.34 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	859.7 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	480 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	600 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, local effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	7 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	11 mg/kg bw/ day	① DNEL worker ② Acute - dermal, systemic effects
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	83 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	14.7 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	208 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, systemic effects
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	11.8 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	4.2 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	4.2 mg/m <sup>3</sup>	① DNEL worker ② Long-term - oral, systemic effects
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 9/20

## REDOCOL Correction Lacquer (various colours)

Substance name	DNEL value	① DNEL type ② Exposure route
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	114 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	1,900 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, local effects
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, local effects
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	343 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	206 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	87 mg/kg bw/ day	① DNEL worker ② Long-term - oral, systemic effects
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	87 mg/kg bw/ day	① DNEL worker ② Acute - oral, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	275 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	33 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	33 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	500 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, local effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	796 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	320 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	36 mg/kg bw/ day	① DNEL worker ② Long-term - oral, systemic effects
<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> EC No.: 927-241-2	185 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> EC No.: 927-241-2	77 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> EC No.: 927-241-2	46 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> EC No.: 927-241-2	300 mg/kg bw/ day	① DNEL worker ② Long-term - oral, systemic effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 10/20

## REDOCOL Correction Lacquer (various colours)

Substance name	DNEL value	① DNEL type ② Exposure route
<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> EC No.: 927-241-2	46 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	10 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	700 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>Hydrocarbons, C9, aromatics</b> CAS No.: 64742-95-6 EC No.: 918-668-5	150 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>Hydrocarbons, C9, aromatics</b> CAS No.: 64742-95-6 EC No.: 918-668-5	32 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>Hydrocarbons, C9, aromatics</b> CAS No.: 64742-95-6 EC No.: 918-668-5	25 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>Hydrocarbons, C9, aromatics</b> CAS No.: 64742-95-6 EC No.: 918-668-5	11 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>Hydrocarbons, C9, aromatics</b> CAS No.: 64742-95-6 EC No.: 918-668-5	11 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	310 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	55 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, local effects

Substance name	PNEC Value	① PNEC type
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.18 mg/L	① PNEC aquatic, freshwater
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.018 mg/L	① PNEC aquatic, marine water
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	35.6 mg/L	① PNEC sewage treatment plant
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.981 mg/L	① PNEC sediment, freshwater
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.0981 mg/L	① PNEC sediment, marine water
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.36 mg/L	① PNEC aquatic, intermittent release
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.0903 mg/L	① PNEC soil, freshwater
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	600 µg/L	① PNEC aquatic, freshwater

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 11/20

## REDOCOL Correction Lacquer (various colours)

Substance name	PNEC Value	① PNEC type
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	60 µg/L	① PNEC aquatic, marine water
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	27.5 mg/L	① PNEC sewage treatment plant
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	8.27 mg/kg	① PNEC sediment, freshwater
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	0.83 mg/kg	① PNEC sediment, marine water
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	1.3 mg/kg	① PNEC soil
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1	1.5 mg/L	① PNEC aquatic, intermittent release
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	0.96 mg/L	① PNEC aquatic, freshwater
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	0.76 mg/L	① PNEC aquatic, marine water
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	580 mg/L	① PNEC sewage treatment plant
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	3.6 mg/kg	① PNEC sediment, freshwater
<b>ethanol</b> CAS No.: 64-17-5 EC No.: 200-578-6	0.63 mg/kg	① PNEC soil, freshwater
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	635 µg/L	① PNEC aquatic, marine water
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	63.5 µg/L	① PNEC aquatic, marine water
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	100 mg/L	① PNEC sewage treatment plant
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	3.29 mg/kg	① PNEC sediment, freshwater
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	0.329 mg/kg	① PNEC sediment, marine water
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	0.29 mg/kg	① PNEC soil
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	6.35 mg/L	① PNEC aquatic, intermittent release
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	0.127 mg/L	① PNEC aquatic, freshwater
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	1 mg/L	① PNEC aquatic, marine water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 12/20

## REDOCOL Correction Lacquer (various colours)

Substance name	PNEC Value	① PNEC type
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/L	① PNEC sewage treatment plant
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	1,000 mg/kg	① PNEC sediment, freshwater
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/kg	① PNEC sediment, marine water
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	1,667 mg/kg	① PNEC secondary poisoning
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	0.61 mg/L	① PNEC aquatic, intermittent release
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/kg	① PNEC soil, freshwater
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	400 µg/L	① PNEC aquatic, freshwater
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	40 µg/L	① PNEC aquatic, marine water
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	10 mg/L	① PNEC sewage treatment plant
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	1.56 mg/kg bw/day	① PNEC sediment, freshwater
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	156 mg/kg bw/ day	① PNEC sediment, marine water
<b>2-methylpropan-1-ol</b> CAS No.: 78-83-1 EC No.: 201-148-0	11 mg/L	① PNEC aquatic, intermittent release

### \* 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. generation/formation of aerosols: Technical ventilation of workplace.

#### 8.2.2. Personal protection equipment



##### Eye/face protection:

In normal use (no eye contact): No goggles required. Eye glasses with side protection EN 166

##### Skin protection:

Tested protective gloves must be worn EN ISO 374.

In full contact: Suitable material: Butyl caoutchouc (butyl rubber), Thickness of the glove material >0,7 mm, Breakthrough time: >480 min.

In splash contact: Suitable material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber), Thickness of the glove material >0,4 mm, Breakthrough time: >120 min.

In normal use (no skin contact): No gloves required.

In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 13/20

## REDOCOL Correction Lacquer (various colours)

### Respiratory protection:

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Thermal hazards:

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Other protection measures:

Wear suitable protective clothing.

### 8.2.3. Environmental exposure controls

No data available

## SECTION 9: Physical and chemical properties

### \* 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state: Liquid

Colour: by respective labeling.

Odour: ester

#### Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		
Melting point	<i>No data available</i>		
Freezing point	<i>No data available</i>		
Initial boiling point and boiling range	114 - 128 °C		
Flash point	14 °C		
Evaporation rate	<i>No data available</i>		
Auto-ignition temperature	370 °C		
Upper/lower flammability or explosive limits	<i>No data available</i>		
Vapour pressure	<i>No data available</i>		
Vapour density	<i>No data available</i>		
Density	0.9 g/cm <sup>3</sup>	20 °C	
Bulk density	<i>not applicable</i>		
Water solubility	partially miscible		
Dynamic viscosity	<i>No data available</i>		
Kinematic viscosity	<i>No data available</i>		

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions /Exothermic reaction with: Strong acid, Base, Oxidising agent, strong.

### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 10.5. Incompatible materials

Oxidising agent.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Flammable solvent vapor mixtures are possible.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 14/20

## REDOCOL Correction Lacquer (various colours)

Gases/vapours, toxic.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1
<b>LD<sub>50</sub> oral:</b> 10,760 mg/kg (Ratte) OECD Prüfrichtlinie 423
<b>LD<sub>50</sub> dermal:</b> >14,112 mg/kg (Rabbit) OECD Prüfrichtlinie 402
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 23.4 mg/L 4 h (Rat) OECD Prüfrichtlinie 403
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1
<b>ATE (inhalation, vapour)<sup>1</sup>:</b> 11 mg/L
<b>LD<sub>50</sub> oral:</b> >2,000 - ≤5,000 mg/kg (Rat) MSDS Distributor
<b>LD<sub>50</sub> dermal:</b> >5,000 mg/kg (Rabbit) MSDS Distributor
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> >10 - ≤20 mg/L 4 h (Rat)
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9
<b>LD<sub>50</sub> oral:</b> 8,530 mg/kg (Ratte) Dow Chemical Company Reports. Vol. MSD-1582
<b>LD<sub>50</sub> dermal:</b> >5,000 mg/kg (Kaninchen) Dow Chemical Company Reports. Vol. MSD-1582
<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> EC No.: 927-241-2
<b>LD<sub>50</sub> oral:</b> >15,000 mg/kg (Rat) MSDS Distributor
<b>LD<sub>50</sub> dermal:</b> >5,000 mg/kg (Rabbit) MSDS Distributor
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> >6.1 mg/L 4 h (Rat) MSDS Distributor
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5
<b>LD<sub>50</sub> oral:</b> >2,000 - 25,000 mg/kg (Rat) OECD 425
<b>LD<sub>50</sub> dermal:</b> >5,000 mg/kg (Rabbit)
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 3.43 - 6.82 mg/L 4 h (Rat) ECHA
<b>xylylene</b> CAS No.: 1330-20-7 EC No.: 215-535-7
<b>LD<sub>50</sub> oral:</b> 4,300 mg/kg (Rat) AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956.
<b>LD<sub>50</sub> dermal:</b> >1,700 mg/kg (Rabbit) Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974.
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 21.7 mg/L 4 h (Rat) Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974.

<sup>1</sup>: Acute Toxicity Estimate. Harmonised (legal) classification.

#### Acute oral toxicity:

Harmful if swallowed.

#### Acute dermal toxicity:

Based on available data, the classification criteria are not met.

#### Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation:

Causes serious eye irritation.

#### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

#### Carcinogenicity:

May cause cancer. Suspected of causing cancer.

#### Reproductive toxicity:

Based on available data, the classification criteria are not met.

#### STOT-single exposure:

May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 15/20

## REDOCOL Correction Lacquer (various colours)

### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

### Aspiration hazard:

Based on available data, the classification criteria are not met.

### Additional information:

No data available

### 11.2. Information on other hazards

No data available

## SECTION 12: Ecological information

### \* 12.1. Toxicity

<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1
LC <sub>50</sub> : 18 mg/L 4 d (fish, Pimephales promelas) OECD Test Guideline 203
EC <sub>50</sub> : 32 - 44 mg/L 2 d (crustaceans, Daphnia magna)
EC <sub>50</sub> : 246 - 647.7 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) Inhibition of growth rate.
NOEC: 105 - 196 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) Inhibition of growth rate.
NOEC: 23.2 mg/L 21 d (crustaceans)
IC <sub>50</sub> : 356 mg/L 2 d (Tetrahymena)
<b>4-methylpentan-2-one</b> CAS No.: 108-10-1 EC No.: 203-550-1
LC <sub>50</sub> : >100 mg/L (fish) MSDS Distributor
LC <sub>50</sub> : >100 mg/L (crustaceans) MSDS Distributor
LC <sub>50</sub> : ≤100 mg/L (Algae/water plant) MSDS Distributor
EC <sub>50</sub> : >100 mg/L (fish) MSDS Distributor
EC <sub>50</sub> : >100 mg/L (crustaceans) MSDS Distributor
EC <sub>50</sub> : ≤100 mg/L (Algae/water plant) MSDS Distributor
IC <sub>50</sub> : >100 mg/L (fish) MSDS Distributor
IC <sub>50</sub> : >100 mg/L (crustaceans) MSDS Distributor
IC <sub>50</sub> : ≤100 mg/L (Algae/water plant) MSDS Distributor
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9
LC <sub>50</sub> : 100 - 180 mg/L 4 d (fish)
EC <sub>50</sub> : 500 mg/L 2 d (crustaceans)
NOEC: 100 mg/L 4 d (fish)
NOEC: 63.5 mg/L 12 d (fish)
NOEC: 100 mg/L 21 d (crustaceans)
NOEC: 1,000 mg/L 4 d (Algae/water plant)
<b>Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with &lt;2% aromatics</b> EC No.: 927-241-2
LC <sub>50</sub> : 10 - ≤100 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) MSDS Distributor
LC <sub>50</sub> : 10 - ≤100 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) MSDS Distributor
LC <sub>50</sub> : >100 mg/L (Algae/water plant) MSDS Distributor
LC <sub>50</sub> : >1,000 mg/L (Mikroorganismen) MSDS Distributor
LC <sub>50</sub> : >10 - <30 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
EC <sub>50</sub> : >1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) EL 50 SDB BR
EC <sub>50</sub> : >22 - <46 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) EL 50 SDB BR
NOEC: <1 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) NOELR SDB BR

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 16/20

## REDOCOL Correction Lacquer (various colours)

**titanium dioxide** CAS No.: 13463-67-7 EC No.: 236-675-5

**LC<sub>50</sub>**: >0.87 - 1.1 mg/L 4 d (fish, Pimephales promelas) ECHA

**LC<sub>50</sub>**: >100 mg/L 2 d (crustaceans, Daphnia magna) ECHA

**EC<sub>50</sub>**: 100 mg/L 3 d (Algae/water plant, Pseudokirchnerella subcapitata) ECHA

**NOEC**: ≥100 mg/L -∞ h (crustaceans, Hyalella azteca) ECHA

**NOEC**: 0.87 - 1.1 mg/L 12 d (fish) ECHA

**NOEC**: 0.004 - 0.08 mg/L 28 d (fish) ECHA

**NOEC**: 100 mg/L 3 d (Algae/water plant) ECHA

**xylene** CAS No.: 1330-20-7 EC No.: 215-535-7

**LC<sub>50</sub>**: 3.3 - 780 mg/L 4 d (fish) Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212

**LC<sub>50</sub>**: 8.5 - 8.5 mg/L 2 d (crustaceans)

### Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

### \* 12.2. Persistence and degradability

**n-butyl acetate** CAS No.: 123-86-4 EC No.: 204-658-1

**Biodegradation**: Yes, rapidly

**Remark**: 83 % (aerob; Exposure duration: 28 d) (OECD Test Guideline 301D)

**4-methylpentan-2-one** CAS No.: 108-10-1 EC No.: 203-550-1

**Biodegradation**: Yes, rapidly

**2-methoxy-1-methylethyl acetate** CAS No.: 108-65-6 EC No.: 203-603-9

**Biodegradation**: Yes, rapidly

**Remark**: in Water

**Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics** EC No.: 927-241-2

**Biodegradation**: Yes, rapidly

**Remark**: Bioakkumulation potentiell möglich, Schädlich für Fische.

**titanium dioxide** CAS No.: 13463-67-7 EC No.: 236-675-5

**Biodegradation**: Yes, slowly

**Remark**: This pigment is an inorganic substance. Due to its very low solubility in water and its internal character, the substance is not considered bioavailable to sediment and terrestrial organisms.

### 12.3. Bioaccumulative potential

**n-butyl acetate** CAS No.: 123-86-4 EC No.: 204-658-1

**Log K<sub>OW</sub>**: 2.3

**4-methylpentan-2-one** CAS No.: 108-10-1 EC No.: 203-550-1

**Log K<sub>OW</sub>**: 1.31

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

**n-butyl acetate** CAS No.: 123-86-4 EC No.: 204-658-1

**Results of PBT and vPvB assessment**: —

**4-methylpentan-2-one** CAS No.: 108-10-1 EC No.: 203-550-1

**Results of PBT and vPvB assessment**: —

**2-methoxy-1-methylethyl acetate** CAS No.: 108-65-6 EC No.: 203-603-9

**Results of PBT and vPvB assessment**: —

**Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics** EC No.: 927-241-2

**Results of PBT and vPvB assessment**: —

**titanium dioxide** CAS No.: 13463-67-7 EC No.: 236-675-5

**Results of PBT and vPvB assessment**: —



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 17/20

## REDOCOL Correction Lacquer (various colours)

**xylene** CAS No.: 1330-20-7 EC No.: 215-535-7

Results of PBT and vPvB assessment: —

### 12.6. Endocrine disrupting properties

No data available

### 12.7. Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### 13.1.1. Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV

##### Waste code product

08 01 11 \* Waste paint and varnish containing organic solvents or other dangerous substances

\*: Evidence for disposal must be provided.

##### Directive 2008/98/EC (Waste Framework Directive)

HP 3 Flammable

##### Waste code packaging

15 01 05 composite packaging

### Waste treatment options

#### Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

#### Appropriate disposal / Package:

Completely emptied packages can be recycled.





#### Other disposal recommendations:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### 13.2. Additional information

Return to Distributor..

## SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.1. UN number or ID number</b>			
UN 1263	UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>			
Paint	Paint	Paint	Paint
<b>14.3. Transport hazard class(es)</b>			
 3	 3	 3	 3
<b>14.4. Packing group</b>			
II	II	II	II
<b>14.5. Environmental hazards</b>			
No	No	No	No
<b>14.6. Special precautions for user</b>			
<b>Special Provisions:</b> 650	<b>Special Provisions:</b> 650	<b>Limited quantity (LQ):</b> 5 L	<b>Special Provisions:</b> 650
<b>Limited quantity (LQ):</b> 5 L	<b>Limited quantity (LQ):</b> 5 L	<b>EmS-No.:</b> F-E, S-E	<b>Limited quantity (LQ):</b> 5 L

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 18/20

## REDOCOL Correction Lacquer (various colours)

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>Hazard identification number (Kemler No.):</b> 30 <b>Classification code:</b> F1 <b>Tunnel restriction code:</b> (D/E) <b>Remark:</b> -	<b>Classification code:</b> F1 <b>Remark:</b> -	<b>Remark:</b> Stowage Category B	

### 14.7. Maritime transport in bulk according to IMO instruments

not determined.

**Additional information:**

-

## SECTION 15: Regulatory information

### \* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU legislation

##### Restrictions on use:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. According to directive 94/33/EC, juveniles are only allowed to handle this product as long as all effects of dangerous substances are prevented. Observe employment restrictions for women of child-bearing age. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

##### Other regulations (EU):

Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 78.9 weight-%

#### 15.1.2. National regulations

##### [GB] National regulations

##### Other regulations, restrictions and prohibition regulations

Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS)

Regulation 850/2004/EC on persistent organic pollutants (POP)

Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC)

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### \* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
3.2.	Mixtures
8.1.	Control parameters
8.2.	Exposure controls
9.1.	Information on basic physical and chemical properties
12.1.	Toxicity
12.2.	Persistence and degradability
14.3.	Transport hazard class(es)
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 19/20

## REDOCOL Correction Lacquer (various colours)

16.1.	Indication of changes
16.5.	List of relevant hazard statements and/or precautionary statements from sections 2 to 15

### 16.2. Abbreviations and acronyms

AC	Article Category
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM	American Society for Testing and Materials
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC <sub>50</sub>	Effective Concentration 50%
ECHA	European Chemicals Agency
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
IC <sub>50</sub>	Inhibition Concentration 50 %
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC <sub>50</sub>	Lethal (fatal) Concentration 50%
LD <sub>50</sub>	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PC	Product category
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
STP	sewage treatment plant
SU	use category
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

For abbreviations and acronyms, see ECHA: Guidance on information requirements and chemical safety assessment, Chapter R.20 (list of terms and abbreviations).

### 16.3. Key literature references and sources for data

No data available

### 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids ( <i>Flam. Liq. 2</i> )	H225: Highly flammable liquid and vapour.	
Acute toxicity (oral) ( <i>Acute Tox. 4</i> )	H302: Harmful if swallowed.	
Serious eye damage/eye irritation ( <i>Eye Irrit. 2</i> )	H319: Causes serious eye irritation.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 May 2024

Print date: 2 May 2024

Version: 0.7



Page 20/20

## REDOCOL Correction Lacquer (various colours)

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	
Carcinogenicity ( <i>Carc. 2</i> )	H351: Suspected of causing cancer.	
Hazardous to the aquatic environment ( <i>Aquatic Chronic 2</i> )	H411: Toxic to aquatic life with long lasting effects.	

### \* 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

### 16.6. Training advice

No data available

### 16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

\* Data changed compared with the previous version.