

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Icema™ R145/88

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Adhesive

Recommended restrictions  
on use : For industrial use only.

### 1.3 Details of the supplier of the safety data sheet

Company : H.B. Fuller, Isar-Rakoll, S.A.

Address : Estrada Nacional 13  
PT-4486-851 Mindelo - Vila do Conde  
+351 229 288 200

E-mail address of person  
responsible for the SDS : EU-MSDS@hbfuller.com

### 1.4 Emergency telephone number

Emergency telephone number : In case of poisoning:  
GBK-EMTEL International  
Tel.(24h): +49(0)6132/84463 (all languages)

In case of transport accidents:  
Tel.(24h): (001) 352 323 3500 (Infotrac - Contract ID: 90373 /  
GBK)

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758


### Icema™ R145/88

Version 1.0	Revision Date: 30.09.2022	SDS Number: 100000020926	Date of last issue: - Date of first issue: 30.09.2022
----------------	------------------------------	-----------------------------	--

	breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

## 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	:	<p><b>Prevention:</b></p> P201 Obtain special instructions before use. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <p><b>Response:</b></p> P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

#### Hazardous components which must be listed on the label:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[isocyanatobenzene], isocyanate-terminated  
 4,4'-methylenediphenyl diisocyanate  
 4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with 2,4'-diisocyanatodiphenylmethane and [(methylethylene)bis(oxy)]dipropylol  
 Diphenylmethanediisocyanate, polymeric

#### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[isocyanatobenzene], isocyanate-terminated	96328-90-4	Resp. Sens. 1; H334 Skin Sens. 1; H317	>= 20 - < 30
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47-0000	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373	>= 10 - < 20
4,4'-Methylenediphenyl diisocyanate,	75880-28-3	Acute Tox. 4; H332	>= 1 - < 10

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version 1.0      Revision Date: 30.09.2022      SDS Number: 100000020926      Date of last issue: -  
Date of first issue: 30.09.2022

oligomeric reaction products with 2,4'-diisocyanatodiphenylmethane and [(methylethylene)bis(oxy)]dipropanol	500-262-0	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373	
Diphenylmethanediisocyanate, polymeric	9016-87-9 618-498-9 615-005-00-9 01-2119457024-46-0000	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Carc. 2; H351	>= 0,1 - < 1
Substances with a workplace exposure limit :			
barium sulfate	7727-43-7 231-784-4 01-2119491274-35-0000		>= 30 - < 50

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Immediately remove clothing if soiled by product.

Even minimal concentrations of isocyanate can lead to a reaction in sensitised people.

Symptoms that may occur include the following:  
irritation of the eyes, nose, throat and lungs, possibly together with a dry throat, a feeling of chest tightness and breathing difficulties.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Show this safety data sheet to the doctor in attendance.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

- In case of unconsciousness bring patient into stable side position for transport.
- In case of skin contact : Treat affected skin with cotton wool or cellulose. Wash off immediately with plenty of water. Use a mild soap if available. If symptoms persist, call a physician.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting. If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : In instances of existing sensitisation towards isocyanates, a doctor should be consulted with regards to work-related contact with other sensitising substances, or substances which irritate the airway.

Treatment for exposure should be geared towards monitoring symptoms and the patient's clinical condition. It must be ensured that the patient has sufficient ventilation and oxygen supply.

Isocyanates can cause sensitisation of the airways, or asthma-like symptoms (bronchospasms). Delayed breathing symptoms, including lung oedema, may occur.

People who have shown signs of breathlessness after considerable exposure should remain under observation for 24-48 hours.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Alcohol-resistant foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

Unsuitable extinguishing media : Water with a full water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : May release toxic, irritating and/or corrosive gases. In case of fire CO, NOx, isocyanates and traces of HCN can be formed.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Use breathing protection against the effects of fumes/dust/aerosol.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation.

#### 6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Send for recovery or disposal in suitable containers.  
Dispose of contaminated material as waste according to section 13.

#### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapor concentration below the workplace limit, wear an adequate respiratory protective device. Take note of emission threshold. Avoid formation of aerosol. Do not heat the product. Ensure that suitable extractors are available on processing machines. Handle with care. Avoid inhalation and skin contact. Keep eye wash bottle available on working place. Avoid release to the environment. Keep away from children.
- Advice on protection against fire and explosion : In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep dark, cool and dry. Do not freeze.
- Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place.
- Advice on common storage : Keep away from food, drink and animal feedingstuffs.
- Dampness : Keep containers dry and tightly closed to avoid moisture absorption and contamination.

### 7.3 Specific end use(s)

- Specific use(s) : No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
barium sulfate	7727-43-7	TWA (inhalable)	10 mg/m <sup>3</sup>	GB EH40

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version 1.0      Revision Date: 30.09.2022      SDS Number: 100000020926      Date of last issue: -  
Date of first issue: 30.09.2022

		dust)		
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m <sup>3</sup> (as -NCO)	GB EH40
<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>				
		STEL	0,07 mg/m <sup>3</sup> (as -NCO)	GB EH40
<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma</p>				



## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version 1.0      Revision Date: 30.09.2022      SDS Number: 100000020926      Date of last issue: -  
Date of first issue: 30.09.2022

	<p>should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>			
		TWA	0,02 mg/m <sup>3</sup> (NCO)	GB EH40
Further information: Capable of causing occupational asthma.				
		STEL	0,07 mg/m <sup>3</sup> (NCO)	GB EH40
Further information: Capable of causing occupational asthma.				
Diphenylmethanediisocyanate, polymeric	9016-87-9	TWA	0,02 mg/m <sup>3</sup> (as -NCO)	GB EH40
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate</p>			

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version 1.0      Revision Date: 30.09.2022      SDS Number: 100000020926      Date of last issue: -  
Date of first issue: 30.09.2022

	<p>standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>			
		STEL	0,07 mg/m <sup>3</sup> (as -NCO)	GB EH40
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>			
		TWA	0,02 mg/m <sup>3</sup>	GB EH40

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

		(NCO)	
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>		
	STEL	0,07 mg/m3 (NCO)	GB EH40
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for</p>		

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version 1.0      Revision Date: 30.09.2022      SDS Number: 100000020926      Date of last issue: -  
Date of first issue: 30.09.2022

	<p>agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>
--	---

#### Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
4,4'-methylenediphenyl diisocyanate	Workers	Dermal	Acute systemic effects	50 mg/kg
	Workers	Inhalation	Acute systemic effects	0,1 mg/m3
	Workers	Dermal	Local effects	28,7 mg/cm2
	Workers	Inhalation	Local effects	0,1 mg/m3
	Workers	Inhalation	Long-term systemic effects	0,05 mg/m3
	Workers	Inhalation	Local effects	0,05 mg/m3
	Workers	Inhalation	Local effects	0,05 mg/m3

#### Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
4,4'-methylenediphenyl diisocyanate	Fresh water	> 1 mg/l
	Marine water	> 0,1 mg/l
	Soil	> 1 mg/kg
	Sewage treatment plant	> 1 mg/l

## 8.2 Exposure controls

### Engineering measures

Please take care on national and local requirements.

### Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

Remarks : Direct contact with the isocyanate-based product must be avoided by organizational measures.

The glove material has to be impermeable and resistant to the product/the substance/the preparation.  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
The gloves need to be disposed after the penetration time and replaced by new ones.  
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

**For the permanent contact gloves made of the following materials are suitable:**  
If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**  
Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

**As protection from splashes gloves made of the following materials are suitable:**  
Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection : Protective clothing

When carrying out activities where unintentional skin contact with the isocyanate-based product may occur (e.g. during maintenance work, or when opening a barrel), wear long-sleeved protective clothing and gloves.

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758

**Icema™ R145/88**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
- Filter type : For short term use a combination of charcoal filter and particulate filter is recommended.
- Protective measures : Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling the product. Avoid contact with the eyes and skin. Store protective clothing separately. Keep away from food, drink and animal feedingstuffs.
- 

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- Appearance : liquid
- Colour : white
- Odour : characteristic
- Odour Threshold : is not determined
- pH : is not determined
- Melting point/freezing point : is not determined
- Boiling point/boiling range : is not determined
- Flash point : 200 °C
- Evaporation rate : is not determined
- Relative vapour density : is not determined
- Density : 1,50 g/cm<sup>3</sup> (20 °C)
- Solubility(ies)  
Water solubility : partly soluble, reacts with water

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

Partition coefficient: n-octanol/water	:	no data available
Auto-ignition temperature	:	is not determined
Decomposition temperature	:	Not applicable
Viscosity Viscosity, dynamic	:	140.000 mPa.s (20 °C)
Explosive properties	:	Product is not explosive. However, formation of explosive vapour/air mixtures is possible.

#### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No further relevant information available.

### 10.2 Chemical stability

No decomposition if used according to the specifications.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alcohols, amines, aqueous acids and alkalis. Mixture reacts with water resulting in evolution of CO <sub>2</sub> . Evolution of CO <sub>2</sub> in closed containers causes overpressure and produces a risk of bursting.
---------------------	---	---

### 10.4 Conditions to avoid

Conditions to avoid	:	No further relevant information available.
---------------------	---	--

### 10.5 Incompatible materials

Materials to avoid	:	No further relevant information available.
--------------------	---	--

### 10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:  
Nitrogen oxides (NO<sub>x</sub>)  
Isocyanates

Additional information: Open and release pressure carefully with pressurised containers.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Based on available data, the classification criteria are not met.

Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

Acute dermal toxicity : Based on available data, the classification criteria are not met.

##### Components:

#### **4,4'-methylenediphenyl diisocyanate:**

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

#### **Diphenylmethanediisocyanate, polymeric:**

Acute inhalation toxicity : LC50 (Rat): 0,49 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute toxicity estimate: 1,5 mg/l

Test atmosphere: dust/mist

Method: Calculation method

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available



## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

#### 12.4 Mobility in soil

**Product:**

Mobility : Medium: Soil

Remarks: Do not allow product to reach ground water, water bodies or sewage system., Very toxic to aquatic organisms, Toxic effects on fish and plankton, Danger to drinking water if even extremely small quantities leak into soil.

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

No data available

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not dispose of waste into sewer.  
Hand over to disposers of hazardous waste.  
The generation of waste should be avoided or minimized wherever possible.  
Incinerate under controlled conditions in accordance with all local and national laws and regulations.  
Disposal must be made according to official regulations.

Contaminated packaging : Disposal must be made according to official regulations.

---

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

---

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3  4,4'-methylenediphenyl diisocyanate (Number on list 74) Diphenylmethanediisocyanate, polymeric (Number on list 74) dibutyltin dilaurate (Number on list 30)
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
RoHS: 2011/65/EU, Restriction of Hazardous Substances	:	Not applicable

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

---

UK REACH List of substances subject to authorisation : Not applicable  
(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Not applicable

**The components of this product are reported in the following inventories:**

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

REACH : On the inventory, or in compliance with the inventory

TECI : On the inventory, or in compliance with the inventory

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

#### SECTION 16: Other information

##### Full text of H-Statements

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure.

##### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

### Icema™ R145/88

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2022	100000020926	Date of first issue: 30.09.2022

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Contact Point : Prepared by: Global Regulatory Department  
EU-MSDS@hbfuller.com

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN