

AQUENCE KL 071/2

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

SDS No.: 667677

V001.1 Revision: 23.03.2022

printing date: 03.05.2022

Replaces version from: 12.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

AQUENCE KL 071/2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

woodworking adhesive

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0 Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains: 1,2-Benzisothiazol-3(2H)-one; Isothiazolinone mixture 3:1 (CIT/MIT) May

produce an allergic reaction.

Safety data sheet available on request.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration >= 0.1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Adhesive, water-based

Base substances of preparation:

Vinyl acetate copolymer

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
propylene carbonate 108-32-7 203-572-1 01-2119537232-48	1- 3%	Eye Irrit. 2, H319		
1,2-Benzisothiazol-3(2H)-one 2634-33-5 220-120-9 01-2120761540-60	0,005- 0,05% (50 ppm- 500 ppm)	Aquatic Acute 1, H400 Aquatic Chronic 2, H411 Acute Tox. 4, Oral, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 2, Inhalation, H330	Skin Sens. 1; H317; C>=0,05 % ===== M acute = 1	
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9 01-2120764691-48	0,0001- 0,0015 % (1 ppm- 15 ppm)	Acute Tox. 2, Inhalation, H330 Aquatic Chronic 1, H410 Acute Tox. 3, Oral, H301 Acute Tox. 2, Dermal, H310 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Skin Corr. 1C, H314	Eye Irrit. 2; H319; C0,06-<0,6 % Skin Irrit. 2; H315; C0,06-<0,6 % Eye Dam. 1; H318; C>=0,6 % Skin Sens. 1A; H317; C>= 0,0015% Skin Corr. 1C; H314; C>=0,6 % ===== M acute = 100 M chronic = 100	

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

An allergic reaction cannot be excluded after repeated skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hy giene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store frost-free.

Keep away from heat and direct sunlight.

Storage at 15 to 25°C is recommended.

Protect from freezing.

Protect from direct sunlight.

7.3. Specific end use(s) woodworking adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Germany

In gredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category/Remarks	Regulatorylist
Propylene carbonate 108-32-7			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Propylene carbonate 108-32-7	2	8,5	Exposure limit(s):	I If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

$\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Value			Remarks	
	•	mg/l	ppm	mg/kg	others	
Propylene carbonate	aqua (marine	0,09 mg/l				
108-32-7	water)					
Propylene carbonate	aqua	0,9 mg/l				
108-32-7	(freshwater)	7.400 "				
Propylene carbonate	sewage	7400 mg/l				
108-32-7	treatment plant (STP)					
Propylene carbonate	Freshwater -	9 mg/l				
108-32-7	intermittent					
Propylene carbonate 108-32-7	Soil			0,81 mg/kg		
Propylene carbonate	Marine water -	0,9 mg/l				
108-32-7	intermittent					
1,2-Benzisothiazol-3(2H)-one	aqua	0,00403				
2634-33-5	(freshwater)	mg/l				
1,2-Benzisothiazol-3(2H)-one	aqua (marine	0,000403				
2634-33-5 1,2-Benzisothiazol-3(2H)-one	water)	mg/l 0,0011				
2634-33-5	aqua (intermittent releases)	mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sewage treatment plant	1,03 mg/l				
	(STP)					
1,2-Benzisothiazol-3(2H)-one	sediment			0,0499		
2634-33-5	(freshwater)			mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (marine water)			0,00499 mg/kg		
1,2-Benzisothiazol-3(2H)-one	Soil			3 mg/kg		
2634-33-5						
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	aqua	0,00339				
methyl-, mixt. with 2-methyl-3(2H)-	(freshwater)	mg/l				
isothiazolone 55965-84-9						
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	aqua (marine	0,00339				
methyl-, mixt. with 2-methyl-3(2H)-	water)	mg/l				
isothiazolone						
55965-84-9						
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	sewage	0,23 mg/l				
methyl-, mixt. with 2-methyl-3(2H)-	treatment plant					
isothiazolone	(STP)					
55965-84-9 Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	sediment			0,027		
methyl-, mixt. with 2-methyl-3(2H)-	(freshwater)			mg/kg		
isothiazolone	(ITESIIWater)			mg/kg		
55965-84-9						
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	sediment			0,027		
methyl-, mixt. with 2-methyl-3(2H)-	(marine water)			mg/kg		
isothiazolone						
55965-84-9	0.1			0.01 "		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	Soil			0,01 mg/kg		
methyl-, mixt. with 2-methyl-3(2H)-isothiazolone						
55965-84-9						
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-	aqua	0,00339				
methyl-, mixt. with 2-methyl-3(2H)-	(intermittent	mg/l				
isothiazolone	releases)					
55965-84-9						

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Propylene carbonate 108-32-7	Workers	inhalation	Long term exposure - systemic effects		70,53 mg/m3	
Propylene carbonate 108-32-7	Workers	inhalation	Long term exposure - local effects		20 mg/m3	
Propylene carbonate 108-32-7	Workers	dermal	Long term exposure - systemic effects		20 mg/kg	
Propylene carbonate 108-32-7	Workers	dermal	Long term exposure - local effects		10 mg/cm2	
Propylene carbonate 108-32-7	General population	inhalation	Long term exposure - systemic effects		17,4 mg/m3	
Propylene carbonate 108-32-7	General population	inhalation	Long term exposure - local effects		10 mg/m3	
Propylene carbonate 108-32-7	General population	dermal	Long term exposure - systemic effects		10 mg/kg	
Propylene carbonate 108-32-7	General population	oral	Long term exposure - systemic effects		10 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	inhalation	Long term exposure - systemic effects		6,81 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	dermal	Long term exposure - systemic effects		0,966 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	inhalation	Long term exposure - systemic effects		1,2 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	dermal	Long term exposure - systemic effects		0,345 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	Workers	inhalation	Long term exposure - local effects		0,02 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	Workers	inhalation	Acute/short term exposure - local effects		0,04 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	inhalation	Long term exposure - local effects		0,02 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	inhalation	Acute/short term exposure - local effects		0,04 mg/m3	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	oral	Long term exposure - systemic effects		0,09 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	oral	Acute/short term exposure - systemic effects		0,11 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Delivery form dispersion
Colour white
Odor neutral

 $\begin{array}{lll} \mbox{Melting point} & \mbox{Not applicable, Product is a liquid} \\ \mbox{Solidification temperature} & 0 \ ^{\circ}\mbox{C} \ (32 \ ^{\circ}\mbox{F}) \ \mbox{Aqueous solution} \\ \mbox{Initial boiling point} & 100 \ ^{\circ}\mbox{C} \ (212 \ ^{\circ}\mbox{F}) \ \mbox{Aqueous solution} \\ \mbox{Flammability} & \mbox{The product is not flammable.} \end{array}$

Explosive limits Not applicable, The product is not flammable.

Flash point Not applicable, Aqueous solution

Auto-ignition temperature Not applicable, The product is not flammable.

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no

organic peroxide and does not decompose under foreseen

conditions of use 4 - 5 no method

pH (20 °C (68 °F); Conc.: 100 % product;

Solvent: Water)

Viscosity (kinematic) 8.182 - 13.636 mm²/s

(40 °C (104 °F);)

Viscosity, dynamic 9.000 - 15.000 mPa.s no method

()

Solubility (qualitative) Miscible

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable

Mixture

1,1 g/cm3 no method

Vapour pressure 23,4 hPa(aqueous solution)

 $(20~^{\circ}\text{C}~(68~^{\circ}\text{F}))$

Density (20 °C (68 °F))

Relative vapour density: < 1

(20 °C)

Particle characteristics

Not applicable

Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

At higher temperatures acetic acid may be released.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
propylene carbonate 108-32-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	LD50	490 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
propylene carbonate 108-32-7	LD50	> 3.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1,2-Benzisothiazol-3(2H)-	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
one				
2634-33-5				
Isothiazolinone mixture	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
3:1 (CIT/MIT)				
55965-84-9				

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
1,2-Benzisothiazol-3(2H)-	LC50	0,4 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
one						Inhalation Toxicity)
2634-33-5						
Isothiazolinone mixture	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
3:1 (CIT/MIT)		_				Inhalation Toxicity)
55965-84-9						-

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
propylene carbonate 108-32-7	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	moderately irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
propylene carbonate 108-32-7	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)-	corrosive	3 h	rabbit	EPA OPP 81-4 (Acute Eye Irritation)
one				
2634-33-5				
Isothiazolinone mixture	Category 1		rabbit	not specified
3:1 (CIT/MIT)	(irreversible			
55965-84-9	effects on the			
	eye)			

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
propylene carbonate 108-32-7	not sensitising	Patch-Test	human	Patch Test
1,2-Benzisothiazol-3(2H)-	sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
one		test		
2634-33-5				
1,2-Benzisothiazol-3(2H)-	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
one		assay (LLNA)		Local Lymph Node Assay)
2634-33-5				
Isothiazolinone mixture	sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
3:1 (CIT/MIT)		test		
55965-84-9				
Isothiazolinone mixture	sensitising	Mouse local lymphnode	mouse	not specified
3:1 (CIT/MIT)		assay (LLNA)		
55965-84-9				

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study/ Route of administration	Metabolic activation/ Exposure time	Species	Method
propylene carbonate 108-32-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
propylene carbonate 108-32-7	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	in vitro mammalian chromosome aberration test	with and without		EPA OPP 84-2 (Mutagenicity Testing)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
propylene carbonate 108-32-7	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: unspecified		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	not carcinogenic	oral: drinking water	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
1,2-Benzisothiazol-3(2H)-	NOAEL P 112 mg/kg	Two	oral: feed	rat	EPA OPPTS 870.3800
one		generation			(Reproduction and Fertility
2634-33-5	NOAEL F1 56,6 mg/kg	study			Effects)
		-			
	NOAEL F2 56,6 mg/kg				
Isothiazolinone mixture	NOAEL P 30 ppm	Two	oral:	rat	OECD Guideline 416 (Two-
3:1 (CIT/MIT)		generation	drinking		Generation Reproduction
55965-84-9	NOAEL F1 300 ppm	study	water		Toxicity Study)
	NOAEL F2 300 ppm				

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
propylene carbonate 108-32-7	NOAEL 0,1 mg/l	inhalation	13 weeks (93 days) 6 h/d; 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
propylene carbonate 108-32-7	NOAEL > 5.000 mg/kg	oral: gavage	90 days 5 days/week	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 150 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 69 mg/kg	oral: feed	90 days daily	rat	EPA OPP 82-1 (90-Day Oral Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 16,3 mg/kg	oral: drinking water	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 0.34 mg/m3	inhalation: aerosol	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 2,625 mg/kg	dermal	90 d 6 h/d	rat	EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
propylene carbonate 108-32-7	LC50	5.300 mg/l	96 h	Leuciscus idus	DIN 38412-15
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	2,15 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,21 mg/l	30 d	Oncorhynchus mykiss	OECD Guideline 215 (Fish, Juvenile Growth Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

	Value	Value	Exposure time	Species	Method
CAS-No.	type				
propylene carbonate	EC50	> 500 mg/l	48 h	Daphnia magna	OECD Guideline 202
108-32-7					(Daphnia sp. Acute
					Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one	EC50	2,9 mg/l	48 h	Daphnia magna	OECD Guideline 202
2634-33-5					(Daphnia sp. Acute
					Immobilisation Test)
Isothiazolinone mixture 3:1	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202
(CIT/MIT)					(Daphnia sp. Acute
55965-84-9					Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
1,2-Benzisothiazol-3(2H)-one	NOEC	1,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
2634-33-5					magna, Reproduction Test)
Isothiazolinone mixture 3:1	NOEC	0,0036 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
(CIT/MIT)					magna, Reproduction Test)
55965-84-9					

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
propylene carbonate 108-32-7	EC50	> 900 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
propylene carbonate 108-32-7	NOEC	900 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	0,11 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,0403 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,0052 mg/l	48 h	Skelet onema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skelet onema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	S pe cies	Method
CAS-No.	type				
propylene carbonate 108-32-7	EC10	> 10.000 mg/l	17 h		not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	23 mg/l		predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC20	0,97 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Haz ardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
propylene carbonate 108-32-7	inherently biodegradable	aerobic	> 70 %		OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
propylene carbonate 108-32-7	readily biodegradable	aerobic	98 %		OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Rapidly biodegradable	aerobic	80 %	21 d	OECD Guideline 303 A (Simulation TestAerobic Sewage Treatment. A: Activated Sludge Units)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Tempe rature	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	6,62	56 d		not specified	other guideline:
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

12.4. Mobility in soil

Hazardous substances	LogPow	Tempe rature	Method
CAS-No.			
propylene carbonate	-0,41		not specified
108-32-7			
1,2-Benzisothiazol-3(2H)-one	0,7	20 °C	EU Method A.8 (Partition Coefficient)
2634-33-5			
Isothiazolinone mixture 3:1	> -0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
(CIT/MIT)			Method)
55965-84-9			

12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT/vPvB
CAS-No.	
propylene carbonate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
108-32-7	Bioaccumulative (vPvB) criteria.
1,2-Benzisothiazol-3(2H)-one	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2634-33-5	Bioaccumulative (vPvB) criteria.
Isothiazolinone mixture 3:1 (CIT/MIT)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
55965-84-9	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):
Persistent organic pollutants (Regulation (EU) 2019/1021):
VOC content 0 %

(VOCV 814.018 VOC regulation

CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 3: highly hazardous to water (Ordinance on facilities for handling

substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)

Not applicable

Not applicable

Not applicable

Storage class according to TRGS 510: 10

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

Substance with a Union workplace exposure limit
EU EXPLD 1:
Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2
Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:
Substance of very high concern (REACH Candidate List)
PBT:
Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.