Revision: 11.09.2024

Safety data sheet according to UK REACH

Printing date 11.09.2024

Version number 25 (replaces version 24)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
 - Trade name Jowatherm® PUR 608.00
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · Uses advised against Restricted to professional users.
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Jowat SE

Ernst-Hilker-Str. 10 - 14; D - 32758 Detmold

Fon +49 (0)5231 749 0 e-mail: info@jowat.de www.jowat.de

Department issuing data specification sheet:

Environmental management

Tel. +49 5231 749 -5374 / -218 / -5460 / -5592

e-mail: umweltmanagement@jowat.de

· Department providing the information:

Jowat UK Ltd.

Lymedale Business Centre

Lymedale Business Park

Hooters Hall Road

Newcastle-under-Lyme

Staffordshire ST5 9QF

Phone: +44 1782 565265 E-mail: nick.orton@jowat.co.uk

· 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - · Classification according to Regulation (EC) No 1272/2008



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS07 GHS08

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 1)

· Signal word Danger

· Hazard-determining components of labelling:

diphenylmethane diisocyanate

Hazard statements

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a doctor if you feel unwell.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P501 Dispose of contents / container to approved waste disposal or recycling in accordance with

national regulations.

Additional information:

Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: Not applicable.

· **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description:

Hot melt adhesive

Polyurethane resin

· Dangerous components:		
CAS: 26447-40-5	diphenylmethane diisocyanate	1-<5%
EINECS: 247-714-0 registration number: 01-2119457024-46 01-2119457015-45	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	

- Additional information

If any R-phrases (risk-phrases) are listed, please refer for the exact wording to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air and contact physician for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air; consult physician in case of symptoms.

· After skin contact

After contact with the molten product, cool rapidly with cold water.

Do not pull solidified product away from the skin.

Seek medical treatment.

· After eye contact Rinse opened eye for several minutes under running water.

(Contd. on page 3)

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 2)

- · After swallowing In case of persistent symptoms consult physician.
- 4.2 Most important symptoms and effects, both acute and delayed Asthma attacks
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire

Nitrogen oxides (NOx)

Carbon monoxide (CÓ)

Hydrogen cyanide (HCN)

5.3 Advice for firefighters

· Protective equipment:

Put on breathing apparatus.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- **6.2 Environmental precautions:** No special measures required.
- 6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to item 13.

Collect mechanically.

Allow to solidify. Collect mechanically.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Thorough dedusting.

Store in cool, dry place in tightly closed containers.

Ensure that suitable extractors are available on processing machines.

- Information about protection against explosions and fires: Keep breathing equipment ready.
- · 7.2 Conditions for safe storage, including any incompatibilities
 - Storage
 - · Requirements to be met by storerooms and containers: No special requirements.
 - · Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions:

Store under dry conditions.

Protect from humidity and keep away from water.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
 - · Components with critical values that require monitoring in the workplace:
 - Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
 - · Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 4)

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 3)

· Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Standard precautionary measures for handling chemicals are to be observed.

Keep away from food, beverages and animal feed.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of work.

Store protective clothing separately.

Vacuum clean contaminated clothing. Do not blow or brush off contamination.

Do not inhale gases / fumes / aerosols.

Avoid skin contact with the liquefied material.

Do not eat or drink while working.

· Breathing equipment:

Use breathing protection in case of insufficient ventilation (EN 149).

Filter A/B/P2.

· Hand protection

Heat resistant gloves

Impervious gloves (EN 374).

· Material of gloves

Leather gloves

Strong gloves

- · Penetration time of glove material No special requirements.
- · Eye/face protection Safety glasses

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Solid.

· Colour: According to product specification

Smell: CharacteristicOdour threshold: Not determined.

• Melting point/freezing point: 65 °C

Boiling point or initial boiling point and boiling

range Not determined

· Flammability Product is not inflammable.

Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

Flash point: >200 °C
 Auto-ignition temperature: 520 °C
 Decomposition temperature: > 250 °C
 pH Not applicable.

· Viscosity:

Kinematic viscositydynamic:Not applicable.Not applicable.

· Solubility

Water: Unsoluble
 Partition coefficient n-octanol/water (log value) Not determined.
 Vapour pressure: Not applicable.

< 0,01 hPa

· Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 Not determined.
 Not applicable.

· 9.2 Other information

· VOC - Volatile Organic Compounds

• European Union 0.00 % • Switzerland 0.00 %

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 4)

	(Conta. nom page 1)
· U.S.A (less water and less exempts)	0.0 g/l / 0.00 lb/gal
Appearance:	Calid
· Form:	Solid.
 Important information on protection of health and environment, and on safety. 	
· Spontaneous combustion:	Product does not undergo spontaneous
	combustion.
Explosive properties:	Product is not explosive.
· Solvent content:	'
Solid content:	100.0 %
Change in condition	
· Evaporation rate	Not applicable.
Information with regard to physical hazard	
classes	
· Explosives	not applicable
Flammable gases	not applicable
Aerosols	not applicable
· Oxidising gases	not applicable
· Gases under pressure	not applicable
· Flammable liquids	not applicable
· Flammable solids	not applicable
 Self-reactive substances and mixtures 	not applicable
· Pyrophoric liquids	not applicable
Pyrophoric solids	not applicable
Self-heating substances and mixtures	not applicable
Substances and mixtures, which emit	
flammable gases in contact with water	not applicable
Oxidising liquids	not applicable
Oxidising solids	not applicable
Organic peroxides	not applicable
Corrosive to metals	not applicable
Desensitised explosives	not applicable

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point

Reacts with water

Reacts with moist air

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Nitrous vitriol gases

Hydrogen cyanide (prussic acid)

Isocyanate

Inflammable gases/vapours

Carbon monoxide and carbon dioxide

Danger of toxic pyrolysis products

Nitrogen oxides (NOx)

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 5)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if inhaled.

· LD/LC50 values that are relevant for classification:		
Inhalative LC50 / 4 h	12 mg/l (rat) (Vapor)	

26447-40-5 diphenylmethane diisocyanate Oral LD50 oral 10,000 mg/kg (rat) Dermal LD50 dermal 10,000 mg/kg (rabbit)

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Carcinogenicity Suspected of causing cancer.
- · 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
26447-40-5 diphenylmethane diisocyanate		
LC0	>1,000 mg/l (zebrafish)	
EC50 / 24 h	>1,000 mg/l (water flea)	
EC50 / 3 h	>100 mg/l (pseudomonas putida)	

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
 - · Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow the product to reach ground water, open water or the sewer system, undiluted or in large quantites.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

- · Recommendation Hand over to disposers of hazardous waste.
- Uncleaned containers/packaging material:
 - · Recommendation:

Non contaminated packagings can be reused.

Non contaminated packagings can be used for recycling.

Packaging with cured adhesive residues can be recycled.

Packaging with cured adhesive residues can be treated as household waste.

(Contd. on page 7)

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 6)

SECTION 14: Transport information			
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	not applicable		
· 14.2 UN proper shipping name · ADR	not applicable not applicable		
· ADN, IMDG, IATA	not applicable		
· 14.3 Transport hazard class(es)			
· ADR, ADN, IMDG, IATA · Class	not applicable		
· 14.4 Packing group · ADR, IMDG, IATA	not applicable		
· 14.5 Environmental hazards:	Not applicable.		
· 14.6 Special precautions for user	Not applicable.		
· 14.7 Maritime transport in bulk according instruments	ing to IMO Not applicable.		
· UN "Model Regulation":	not applicable		

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 - · Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

These data are based on our present knowledge. They shall, however, not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

All standard industrial precautions apply, concerning protection of health, and safe handling. The recommendations have to be examined in the context of the application for which the product is intended, and observed as necessary.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH204 Contains isocyanates. May produce an allergic reaction.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 7)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· * Data modified in comparison to the previous version.

(Contd. on page 9)

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 8)

Annex: Exposure scenario 1

- · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- · Product category PC1 Adhesives, sealants
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring

PROC15 Use as laboratory reagent

PROC14 Tabletting, compression, extrusion, pelletisation, granulation

PROC21 Low energy manipulation and handling of substances bound in/on materials or articles

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use Customary application according to section 1.
 - · Duration and frequency 8hrs (full working shift).
- Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity 33333 tons per day
- · Other operational conditions Observe the standard safety regulations when handling chemicals
 - · Other operational conditions affecting environmental exposure

The product must not get in contact with soil, surface water and ground water before complete hardening.

Observe section 6 of the Safety Data Sheet (Accidental release measures).

High temperatures promote emission.

Other operational conditions affecting worker exposure

Avoid long-term or repeated skin contact.

Avoid contact with the skin and eyes.

Respiratory protection is required in work areas with inadequate ventilation and during spraying application.

Ensure adequate ventilation, especially in closed rooms.

Avoid contact with eyes.

Avoid contact with the skin.

Avoid breathing particles.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

· Worker protection

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · Organisational protective measures Provide Internal Plant Instruction.
- Technical protective measures

Ensure that suitable extractors are available on processing machines.

· Personal protective measures

Use breathing protection in case of insufficient ventilation (EN 149).

Use breathing protection in case of insufficient ventilation (EN 14387).

Printing date 11.09.2024

Version number 25 (replaces version 24)

Trade name Jowatherm® PUR 608.00

(Contd. from page 9)

Revision: 11.09.2024

Filter A/B/P2.

In case of brief exposure or low pollution use breathing filter apparatus (EN 136). In case of intensive or longer exposure use breathing apparatus that is independent of circulating air (EN 137). Heat resistant gloves

Impervious gloves (EN 374).

- · Measures for consumer protection Ensure adequate labelling.
- · Environmental protection measures
 - · Air No special measures required.
 - · Water Do not allow to reach sewage system.
 - · Soil No special measures required.
 - · Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.
- Disposal measures Ensure that waste is collected and contained.
 - · Disposal procedures

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Waste type

Partially emptied and uncleaned packaging

Solid product residues

- · Exposure estimation
 - · Worker (oral) No significant oral exposure
 - · Worker (dermal) No significant dermal exposure
 - Worker (inhalation) The calculated value is smaller than the DNEL.
 - Environment The calculated value is smaller than the PNEC.
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

(Contd. on page 11)

Printing date 11.09.2024 Version number 25 (replaces version 24) Revision: 11.09.2024

Trade name Jowatherm® PUR 608.00

(Contd. from page 10)

Annex: Exposure scenario 2

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC1 Adhesives, sealants
- · Process category

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring

PROC11 Non industrial spraying

PROC14 Tabletting, compression, extrusion, pelletisation, granulation

PROC15 Use as laboratory reagent

PROC21 Low energy manipulation and handling of substances bound in/on materials or articles

Environmental release category

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use Customary application according to section 1.
- · **Duration and frequency** 8hrs (full working shift).
- · Worker 8hrs (full working shift).

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- Physical state Solid.
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity 8000 kg per day
- Other operational conditions Observe the standard safety regulations when handling chemicals
 - Other operational conditions affecting environmental exposure

Observe section 6 of the Safety Data Sheet (Accidental release measures).

The product must not get in contact with soil, surface water and ground water before complete hardening.

High temperatures promote emission.

Other operational conditions affecting worker exposure

Indoor application.

Outdoor application.

Avoid contact with eyes.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Avoid breathing particles.

- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

· Worker protection

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · Organisational protective measures Provide Internal Plant Instruction.
- Technical protective measures

Ensure that suitable extractors are available on processing machines.

Printing date 11.09.2024 Version number 25 (replaces version 24)

Trade name Jowatherm® PUR 608.00

(Contd. from page 11)

Revision: 11.09.2024

· Personal protective measures

Use breathing protection in case of insufficient ventilation (EN 149).

Filter A/B/P2.

In case of brief exposure or low pollution use breathing filter apparatus (EN 136). In case of intensive or longer exposure use breathing apparatus that is independent of circulating air (EN 137). Heat resistant gloves

Impervious gloves (EN 374).

- Measures for consumer protection Ensure adequate labelling.
- Environmental protection measures No special measures required.
 - · Air No special measures required.
 - · Water Do not allow to reach sewage system.
 - · Soil No special measures required.
 - · Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.
- Disposal measures Ensure that waste is collected and contained.
 - · Disposal procedures

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Waste type

Solid product residues

Partially emptied and uncleaned packaging

- **Exposure estimation**
 - · Worker (oral) No significant oral exposure
 - · Worker (inhalation) The calculated value is smaller than the DNEL.
 - · Environment The calculated value is smaller than the PNEC.
 - · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.