according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3



REDOCOL Modeling spatula

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

REDOCOL Modeling spatula

Article No.:

MO10200

UFI:

NR7W-S028-U000-03J4

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Bodyfiller/stopper

Relevant identified uses:

Life cycle stage [LCS]

IS: Use at industrial sites

Sector of uses [SU]

SU 18: Manufacture of furniture

Product Categories [PC]

PC 9b: Fillers, putties, plasters, modelling clay

Article categories [AC]

AC 11e: Wood articles: Furniture & furnishings

1.3. Details of the supplier of the safety data sheet

distributor: Supplier:

Ostermann UK Ltd Stonebridge Cross Business Park

Unit 104 Pointon Way

WR9 0LW Droitwich United Kingdom

Telephone: UK +44 (0) 1905 793 550, Ireland +44

(0) 1905 793 552

Telefax: +44 (0) 1905 793 559

E-mail: UK sales.uk@ostermann.eu, Ireland

sales.ie@ostermann.eu

Website: www.ostermann.eu

E-mail (competent person): sds@ostermann.eu

1.4. Emergency telephone number

UK: For non-emergency personnel: +44 1905 793 550

IR: For non-emergency personnel: +44 1905 793 552, 24h: +49 30 - 30 68 67 00 (National Poison Inform. Centre Berlin), UK +44 1905 793 550 / IR +44 (0)1905 793 552 (Only available during office hours.)

FSG Schäfer GmbH

Telephone: +49 (0) 25 63 - 93 95 - 0

Telefax: +49 (0) 25 63 - 93 95 - 25 **E-mail:** verkauf@fsg-schaefer.de

Website: www.fsg-schaefer.de

Boschstraße 14

GERMANY

48703 Stadtlohn

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 3)	H226: Flammable liquid and vapour.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Reproductive toxicity (Repr. 2)	H361d: Suspected of damaging the unborn child.	

en / GB / IE

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3



REDOCOL Modeling spatula

Hazard classes and hazard categories	Hazard statements	Classification procedure
	H372: Causes damage to organs through prolonged or repeated exposure. (auditory organs)	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:







GHS07 Exclamation mark



Health hazard

Signal word: Danger

Hazard statements for physical hazards	
H226	Flammable liquid and vapour.

Hazard statements for health hazards		
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H361d	Suspected of damaging the unborn child.	
H372	Causes damage to organs through prolonged or repeated exposure. (auditory organs)	

Precautionary statements		
P101 If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.	

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ Personal protection.	

Precautionary state	Precautionary statements Response		
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P308 + P313	IF exposed or concerned: Get medical advice/attention.		
P370 + P378	In case of fire: Use Jet of water spray; alcohol resistant foam; carbon dioxide (CO2); extinguishing powder. Class B fire extinguishers. to extinguish.		

Precautionary statements Storage	
P405	Store locked up.

Precautionary statements Disposal		
P501 Dispose of contents/container to Disposal methods.		

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Mixture of following listed substances with nonhazardous additions.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3 Page 3/11



REDOCOL Modeling spatula

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 100-42-5 EC No.: 202-851-5 Index No.: 601-026-00-0	styrene Acute Tox. 4 (H332), Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), Repr. 2 (H361d), STOT RE 1 (H372), Skin Irrit. 2 (H315)	≥ 25 - < 50 weight-%
	ATE (inhalation, vapour) 12 mg/L	

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Self-protection of the first aider. Take off contaminated clothing and wash it before reuse.

Following inhalation:

Provide fresh air. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. If eye irritation persists: Get medical advice/attention.

Following ingestion:

Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide (CO2), Extinguishing powder, Water spray jet.

In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

Hazardous combustion products:

In case of fire: Carbon monoxide, Carbon dioxide (CO2).

5.3. Advice for firefighters

Do not inhale explosion and combustion gases.

In case of fire: Wear self-contained breathing apparatus.

Cool endangered containers by spraying with water.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3



REDOCOL Modeling spatula

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Personal protection equipment: see section 8

Emergency procedures:

Escape route

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Recycle according to official regulations. Provide adequate ventilation.

6.4. Reference to other sections

Safe handling: see section 7.

Personal protection equipment: see section 8.

Disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Fire prevent measures:

Keep away from sources of ignition - No smoking.

Measures to prevent aerosol and dust generation:

Provide adequate ventilation as well as local exhaustion at critical locations.

Environmental precautions:

Cover drains.

Advices on general occupational hygiene

Do not eat, drink or smoke when using this product. Do not breathe gas/fumes/vapour/spray. Wash hands thoroughly after handling. After cleaning apply high-fat content skin care cream.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed and in a well-ventilated place.

Packaging materials:

Keep container tightly closed.

Avoid high temperatures or direct sunlight.

Requirements for storage rooms and vessels:

Provide for retaining containers, e.g. floor pan without outflow.

Hints on storage assembly:

Keep away from: Oxidizing agent.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

Industrial sector specific solutions:

Putty, based on calcium sulphate

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3



REDOCOL Modeling spatula

GISCODE:

CP1

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
IE	styrene CAS No.: 100-42-5 EC No.: 202-851-5	① 20 ppm (85 mg/m³) ② 40 ppm (170 mg/m³)
WEL (GB)	styrene CAS No.: 100-42-5 EC No.: 202-851-5	① 100 ppm (430 mg/m³) ② 250 ppm (1,080 mg/m³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
styrene CAS No.: 100-42-5 EC No.: 202-851-5	85 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	1 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	100 mg/m ³	DNEL worker Acute - inhalation, systemic effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	10 mg/m³	DNEL Consumer Acute - inhalation, systemic effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	100 mg/m ³	① DNEL worker ② Long-term – inhalation, local effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	1 mg/m³	① DNEL Consumer ② Long-term – inhalation, local effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	100 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	10 mg/m³	DNEL Consumer Acute - inhalation, local effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	406 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
styrene CAS No.: 100-42-5 EC No.: 202-851-5	343 mg/kg bw/ day	DNEL Consumer Long-term - dermal, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 **Print date:** 16 Jun 2024

Version: 0.3



REDOCOL Modeling spatula

Substance name		① DNEL type ② Exposure route
styrene CAS No.: 100-42-5 EC No.: 202-851-5	hw/day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
styrene CAS No.: 100-42-5 EC No.: 202-851-5	40 μg/L	① PNEC aquatic, freshwater
styrene CAS No.: 100-42-5 EC No.: 202-851-5	40 μg/L	① PNEC aquatic, marine water
styrene CAS No.: 100-42-5 EC No.: 202-851-5	5 mg/L	① PNEC sewage treatment plant
styrene CAS No.: 100-42-5 EC No.: 202-851-5	0.614 mg/kg	① PNEC sediment, freshwater
styrene CAS No.: 100-42-5 EC No.: 202-851-5	0.418 mg/kg	① PNEC sediment, marine water
styrene CAS No.: 100-42-5 EC No.: 202-851-5	0.2 mg/kg	① PNEC soil
styrene CAS No.: 100-42-5 EC No.: 202-851-5	40 μg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

8.2.2. Personal protection equipment





Eye/face protection:

EN 166.

Skin protection:

Tested protective gloves must be worn. EN ISO 374. When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Recommended material: NBR (Nitrile rubber), Thickness of the glove material: >0,4 mm.

Permeation time (maximum wear duration): Observe instructions for use.

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. Filter type: A2

Other protection measures:

Keep away from: Food and feedingstuffs, Wash hands before breaks and after work. Do not breathe gas/fumes/vapour/spray.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: various

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3



REDOCOL Modeling spatula

Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
рН	No data available		
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	145 °C		② MSDS Distributor
Flash point	34 °C		② MSDS Distributor
Evaporation rate	No data available		
Auto-ignition temperature	480 °C		② MSDS Distributor
Upper/lower flammability or explosive limits	1.2 - 8.9 Vol-%		② The product is not explosive, however, formation of explosive / ignitable vapor / air mixtures is possible.
Vapour pressure	7 hPa	20 °C	② MSDS Distributor
Vapour density	No data available		
Density	1.11 g/cm³	20 °C	② MSDS Distributor
Bulk density	not applicable		
Water solubility	Immiscible		② MSDS Distributor
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

styrene CAS No.: 100-42-5 EC No.: 202-851-5

LD₅₀ **oral:** 2,650 mg/kg (Rat) Science Reports of the Research Institutes, Tohoku University, Series C: Medicine. Vol. 36(1-4), Pg. 10, 1989.

LC₅₀ Acute inhalation toxicity (vapour): 12 mg/L 4 h (Rat) Archives of Environmental Health. Vol. 18, Pg. 878, 1969.

Acute dermal toxicity:

Causes skin irritation.

Skin corrosion/irritation:

Causes skin irritation.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3 Page 8/11



REDOCOL Modeling spatula

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Suspected of damaging the unborn child.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

styrene CAS No.: 100-42-5 EC No.: 202-851-5

LC₅₀: 4.02 – 74.8 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) Pickering, Q.H., and C. Henderson 1966. Acute Toxicity of Some Important Petrochemicals to Fish. J.Water Pollut.Control Fed. 38(9):1419-1429

LC₅₀: 23 – 59 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) LeBlanc, G.A. 1980. Acute Toxicity of Priority Pollutants to Water Flea (Daphnia magna). Bull.Environ.Contam.Toxicol. 24(5):684-691 (OECDG Data File); Qureshi, A.A., K.W. Flood, S.R. Thompson, S.M. Janhurst, C.S. Inniss, and D.A. Rokosh 1982. Compariso

EC₅₀: 4.7 – 4.7 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) Cushman, J.R., G.A. Rausina, G. Cruzan, J. Gilbert, E. Williams, M.C. Harrass, J.V. Sousa, A.E. Putt, N.A. Garvey, J.P. 1997. Ecotoxicity Hazard Assessment of Styrene. Ecotoxicol.Environ.Saf. 37:173-180

EC₅₀: 1.4 – 1.4 mg/L 3 d (Algae/water plant) Cushman, J.R., G.A. Rausina, G. Cruzan, J. Gilbert, E. Williams, M.C. Harrass, J.V. Sousa, A.E. Putt, N.A. Garvey, J.P.1997. Ecotoxicity Hazard Assessment of Styrene. Ecotoxicol.Environ.Saf. 37:173-180

Aquatic toxicity:

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

styrene CAS No.: 100-42-5 EC No.: 202-851-5

Biodegradation: Yes, slowly

Remark: No indication of bioaccumulation potential.

Abiotic degradation:

Based on available data, the classification criteria are not met.

Biodegradation:

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

styrene CAS No.: 100-42-5 EC No.: 202-851-5

Log Kow: 2.96

Accumulation / Evaluation:

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3



REDOCOL Modeling spatula

12.5. Results of PBT and vPvB assessment

styrene CAS No.: 100-42-5 EC No.: 202-851-5
Results of PBT and vPvB assessment: —

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Non-contaminated packages may be recycled.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

08 04 09 * Waste adhesives and sealants containing organic solvents or other dangerous substances

*: Evidence for disposal must be provided.

Waste code packaging

15 01 10 * packaging containing residues of or contaminated by dangerous substances

*: Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

to local disposal.

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

Other disposal recommendations:

Return to Distributor...

SECTION 14: Transport information

Land transport (ADR/RID) Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number	•	·
UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shi	pping name		
PAINT Solution (Styrene)	PAINT Solution (Styrene)	PAINT Solution (Styrene)	PAINT Solution (Styrene)
14.3. Transport haz	ard class(es)		,
		· ·	*
3	3	3	3
14.4. Packing group)		
III	III	III	III
14.5. Environmenta	l hazards		
not determined	not determined	not determined	not determined
14.6. Special preca	utions for user		
Special Provisions: 650	Special Provisions: 650	Special Provisions: 5L	Special Provisions: 5 L
Limited quantity (LQ): 5 L	Limited quantity (LQ): 5 L	EmS-No.: F-E, S-E	
Hazard identification number (Kemler No.): 30	Classification code: F1		
Classification code: F1			en / GB / l

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3 Page 10/11



REDOCOL Modeling spatula

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
Tunnel restriction code: (D/E)			

14.7. Maritime transport in bulk according to IMO instruments

not determined

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions): 3.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P5c FLAMMABLE LIQUIDS.

Other regulations (EU):

Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

VOC content: 0%.

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

16.1. Indication of changes

16.2. Abbreviations and acronyms

AC Article Category

ACGIH American Conference of Governmental Industrial Hygienists

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DIN German Institute for Standardization / German Industrial Standard

DNEL derived no-effect level EC₅₀ Effective Concentration 50% ECHA European Chemicals Agency

EN European Standard ES Exposure scenario

EWC European Waste Catalogue

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

KG body weight

LC₅₀ Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

MAK Maximum concentration in the workplace air (CH)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

OEL Threshold Limit Value

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2024 Print date: 16 Jun 2024

Version: 0.3 Page 11/11



REDOCOL Modeling spatula

OSHA Occupational Safety & Health Administration PBT persistent and bioaccumulative and toxic

PC Product category

PNEC Predicted No Effect Concentration

REACH Registration, Evaluation and Authorization of Chemicals RID Dangerous goods regulations for transport by rail

SU use category

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 3)	H226: Flammable liquid and vapour.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Reproductive toxicity (Repr. 2)	H361d: Suspected of damaging the unborn child.	
STOT-repeated exposure (STOT RE 1)	H372: Causes damage to organs through prolonged or repeated exposure. (auditory organs)	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements		
H226	Flammable liquid and vapour.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H361d	Suspected of damaging the unborn child.	
H372	Causes damage to organs through prolonged or repeated exposure.	

16.6. Training advice

No data available

16.7. Additional information

The information provided in this safety data sheet is correct to the best of our knowledge at the time of going to press. This information is intended to provide guidance for the safe handling, storage, processing, transport and disposal of the product mentioned in this safety data sheet. The information is not transferable to other products. If the product is mixed with other materials, mixed or processed, or subjected to processing, the data contained in this safety data sheet can not be transferred to the new material thus produced unless otherwise expressly stated otherwise.

^{*} Data changed compared with the previous version.