

MS-POLYMER 660.00/01

REDOCOL MS-Polymer 660.00/01 is a ready-to-use, high-quality assembly glue based on MS-Polymer. REDOCOL MS-Polymer 660.00/01 is suitable for sealing joints as well. The adhesive can be painted over, stays elastic and has a high initial strength.

- Suitable for a number of materials
- Bonding and sealing at the same time
- High initial tack
- Waterproof
- Stays elastic
- Can be painted over
- Colourfast
- Solvent-free
- Available colours: transparent/white

Application areas

Suitable for bonding nearly all materials like (natural) stone, concrete, mirrors, cement, PVC, various plastics, metal, aluminium, copper, lead, zinc, wood, glass and compact boards. Suitable as water-resistant sealant.

Application

Surfaces for bonding must be clean, dust- and grease-free. Apply REDOCOL MS-Polymer 660.00/01 and press shortly. Distribute the glue and fix the parts, if needed. Processing is usually possible with standard cartridge guns.

Min. processing temperature:	+5° C
Temperature resistance:	-40° C bis +90° C
Open time:	10 min.
Cure time:	24 h
Skin building time:	approx. 10 min.

Shelf life

In closed condition, REDOCOL MS-Polymer 660.00/01 lasts for 12 months. The adhesive should be stored in a cool and frost-free place.

Packaging

Cartridges with a content of 290 ml.

Please note the safety data sheet!