

# Cleaning Agent 761.7

**Hotmelt material to clean pre-melters in which reactive PUR hotmelt adhesives are processed.**

## Fields of application

- Cleaning of melting and application units with replaceable reactive PUR hotmelt adhesive inserts, and other non-reactive hotmelt adhesive systems (e. g. those based on EVA)

## Advantages

- The use of a hotmelt cleaning agent prevents clogging of feeding systems as well as reactive incrustation on application units. Renders nozzles clog free.
- Good mixture properties with the hotmelt
- Neutralizes the isocyanate reaction
- The same processing temperature as for KLEIBERIT PUR Hotmelts

## Properties of the hotmelt cleaning agent

<b>Base:</b>	EVA Copolymers
<b>Specific gravity:</b>	approx. 0.98 g/cm <sup>3</sup>
<b>Colour:</b>	blue
<b>Viscosity</b>	
<b>Brookfield HBTD:</b>	at 120°C: 11,000 ± 3,000 mPa·s at 140°C: 6,000 ± 2,000 mPa·s
<b>Processing temperature:</b>	120 - 140°C
<b>Identification:</b>	not required according to EU regulations (see our safety data sheet)

## Attention:

When hotmelt adhesives are melted and applied, vapours are set free and an unpleasant odour can occur, even if the recommended working temperature has been observed. Moreover if the prescribed working temperature is exceeded over a longer period, harmful decomposition products can develop. Precautions should be taken to eliminate the vapours, e.g. by using a suitable ventilation system.

## Application techniques

Especially when PUR hotmelt adhesives are used, it is important that the application devices (particularly those devices fitted with nozzles), be thoroughly cleaned when there is a stoppage in the application process, (e.g. overnight or at the weekend).

Thorough cleaning can easily be performed by melting and flushing Cleaning Agent 761.7 through the application device.

## Attention!

Before PUR hotmelt adhesives are again used in these machines, Cleaning Agent 761.7 has to be completely drained off.

## Packaging

carton with 12 aluminium cartridges at 0,25 kg net each  
 carton with 6 foil bags at 1.50 kg net each  
 metal pail, 15 kg net  
 bag, 20 kg net  
 drum, 150 kg net

Additional packaging sizes available upon request.

## Storage

KLEIBERIT Cleaning Agent 761.7 can be stored for approximately 2 years.  
 Keep in a cool and dry place.

Version KH 0213; replaces previous versions

**Waste Disposal**

Disposal of contents and/or containers should comply with all applicable federal, state and local regulations.

Our containers are made of recyclable material.

**Service**

Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation.