



## Technical Data Sheet

BAO-Spray 800

### I. Description of Product

Field of application:	Aerosols for lacquering and restoring of wooden and melamine surfaces.
Colours:	Clear lacquers, tinted & pigmented lacquers, RAL-Colours and colours according to BAO Colour Card 800. We can also produce house colours according to customers' colour match.
Packaging:	Cans in 150, 300 & 500 mls.

### II. Product properties

General:	Clear, tinted and pigmented nitrocellulose lacquers.
Base of solvent:	Different acetates.
Light persistence:	Good.
Paint over:	---

### III. Workmanship

Surface:	The damaged spot has to be dry, clean and free of oil.
Application:	<p>Shake can well one minute before use; ball agitators must be heard well. Test the lacquer on a invisible spot in order to check colour and compatibility of the varnish. Keep can vertical and spray at a distance of about 25-35 cm. Do not spray one heavy coat, but in thin layers. This prevents formation and sagging. Allow 5-15 minutes for drying. Use only at room temperature in well ventilated areas.</p> <p>After use, to keep the valve clear, hold can upside down and spray until only gas secpes. Dirty spray heads can be cleaned with nc-thinner.</p> <p>Pay attention to the safety-instructions on the can.</p>
Storage:	Keep cool and dry in upright position. Shelf-life: 6 months.

**a**

Although the information and recommendations set forth herein are believed to be correct as of the date hereof BAO-CHEMIE makes no representations to the accuracy of such information. It's the user's responsibility to determine the suitability and completeness of such information and recommendations for its own particular use.